

Vector offers the widest range of Vacuum Excavators for the Utility Industry – ranging from single to four-rear axle, 3.5 yd<sup>3</sup> to 15 yd<sup>3</sup> debris capacity, and air, water, or both for digging.

### HXX Paradigm®



| Axle Configuration | Vacuum System | CFM   | Vacuum | Debris Capacity (yds) | Minimum HP | Rated Gross Vehicle Weight (GVW) (lbs) |                        |
|--------------------|---------------|-------|--------|-----------------------|------------|--|------------------------|
| Single             | 6"            | 2,200 | 15"    | 3.3                   | 325        | Class 6 chassis (Non-CDL) 26,000       | Class 7 chassis 33,000 |

Unique Advantages – Compact, low profile, maneuverable design

### HXX Prodigy® 6-Yard



| Axle Configuration | Vacuum System | CFM   | Vacuum | Debris Capacity (yds) | Minimum HP | Rated Gross Vehicle Weight (GVW) (lbs) |  |
|--------------------|---------------|-------|--------|-----------------------|------------|--|--|
| Single             | 6"            | 3,200 | 16"    | 6                     | 300        | 33,000                                 |  |

Unique Advantages – Small, easier to maneuver in confined spaces

### HXX Prodigy® 9-Yard



| Axle Configuration | Vacuum System | CFM   | Vacuum | Debris Capacity (yds) | Minimum HP | Rated Gross Vehicle Weight (GVW) (lbs) |  |
|--------------------|---------------|-------|--------|-----------------------|------------|--|--|
| Tandem             | 6"            | 3,200 | 16"    | 9                     | 330        | 62,000                                 |  |
| Tandem w/ Pusher   | 6"            | 3,200 | 16"    | 9                     | 330        | 70,000                                 |  |

Unique Advantages – Small, easier to maneuver in confined spaces, extreme payload capacity

### HXX PD w/ Roots 824 Blower



| Axle Configuration     | Vacuum System | CFM   | Vacuum | Debris Capacity (yds) | Minimum HP | Rated Gross Vehicle Weight (GVW) (lbs) |  |
|------------------------|---------------|-------|--------|-----------------------|------------|--|--|
| Tandem                 | 8"            | 4,970 | 18"    | 12/15                 | 380        | 66,000                                 |  |
| Tandem w/ Pusher       | 8"            | 4,970 | 18"    | 12/15                 | 380        | 79,500                                 |  |
| Tandem w/ Pusher & Tag | 8"            | 4,970 | 18"    | 12/15                 | 380        | 88,000                                 |  |

Unique Advantages – High payload capacity, cost-effective

### HXX PD w/ Hibon 8702 Blower



| Axle Configuration        | Vacuum System | CFM   | Vacuum | Debris Capacity (yds) | Minimum HP | Rated Gross Vehicle Weight (GVW) (lbs) |  |
|---------------------------|---------------|-------|--------|-----------------------|------------|--|--|
| Tandem w/ Pusher          | 8"            | 5,250 | 28"    | 12/15                 | 425        | 66,000                                 |  |
| Tandem w/ Pusher & Tag    | 8"            | 5,250 | 28"    | 12/15                 | 425        | 88,000                                 |  |
| Tridrive (12 yd)          | 8"            | 5,250 | 28"    | 12/15                 | 425        | 90,000                                 |  |
| Tandem Steer/ Tandem Rear | 8"            | 5,250 | 28"    | 12/15                 | 425        | 86,000                                 |  |

Unique Advantages – Powerful vacuum, versatile all-around machine

### HXX PD w/ Robuschi Blower



| Axle Configuration     | Vacuum System | CFM   | Vacuum | Debris Capacity (yds) | Minimum HP | Rated Gross Vehicle Weight (GVW) (lbs) |  |
|------------------------|---------------|-------|--------|-----------------------|------------|--|--|
| Tandem w/ Pusher       | 8"            | 6,176 | 28"    | 12                    | 500        | 79,500                                 |  |
| Tandem w/ Pusher & Tag | 8"            | 6,176 | 28"    | 12                    | 500        | 88,000                                 |  |
| Tridrive               | 8"            | 6,176 | 28"    | 12                    | 500        | 90,000                                 |  |

Unique Advantages – Powerful vacuum, quieter operation

### HXX Fan



| Axle Configuration     | Vacuum System | CFM | Vacuum | Debris Capacity (yds) | Minimum HP | Rated Gross Vehicle Weight (GVW) (lbs) |  |
|------------------------|---------------|-----|--------|-----------------------|------------|--|--|
| Tandem w/ Pusher       | 8"            |     |        | 12/15                 | 410        | 79,500                                 |  |
| Tandem w/ Pusher & Tag | 8"            |     |        | 12/15                 | 410        | 88,000                                 |  |
| Tridrive               | 8"            |     |        | 12/15                 | 410        | 90,000                                 |  |

Unique Advantages – High payload capacity, more forgiving with less experienced operators

Weights and dimensions shown are for reference only and the actual will vary based on option content and chassis selected. Some images may include optional equipment. Specifications subject to change without notice. Vector®, HXX® HydroExcavator®, and HXX Prodigy®, ParaDIGm® are registered trademarks of Vector Manufacturing. Vector is a subsidiary of Federal Signal.

Effective 5/17 P/N 00077-E ©2017 Vector Manufacturing